

SHAMROCKWOOD315

NubHex3 and Nubhex Guide

Introduction

NubHex3 and Nubhex are versatile tools ideal for both in-shop and on-the-go applications, designed to accommodate the most common hex bolt sizes: 3mm, 4mm, and 5mm.

Important Considerations

- **Chemical Compatibility:** Avoid using NubHex3 and Nubhex with harsh cleaning chemicals such as acetone or mineral spirits.
- **Temperature:** These tools are not designed for use in high-temperature applications or environments.
- **Torque Limits:** Avoid excessive torque when using NubHex3 and Nubhex. Too much force can cause the hex bit to turn slightly in the housing, potentially requiring pliers for removal.
- **Bit Insertion (NubHex3):** Do not insert the main hex bit beyond the indicated line on the bit. These tools utilize a friction fit, and full insertion can make bit changes more difficult.

Troubleshooting

- **Stiff Bits:** In some cases, such as during shipping or in colder temperatures, the hex bits may become stiff and difficult to remove. For the main bit, use pliers or vice grips to gently pull the bit out and then slide it back in several times. If the other bits are tight, carefully use a screwdriver to push them out. With use, the bits will loosen slightly over time.

Thank You

Thank you for your support.

Bryan Blake - Shamrockwood315.com